

CLEANING AND MAINTENANCE RECOMMENDATIONS

Color Quartz Flooring - Cleaning should be accomplished using a non-filming detergent such as APF Orange Clean. Avoid abrasive cleaners that may dull the surface. Smoother texture floors may be mopped. Slip-resistant floors must be cleaned using a stiff-bristled broom or a floor machine with a medium brush. Paint thinner may be used for spot cleaning. Periodic resin recoating may be done to restore the new appearance. Epoxy and polyurethane may be used with polyurethane providing the better finish. This should be done in strict accordance with the manufacturer's written instructions.

Seamless Color Chip Flooring - Cleaning should be accomplished using a non-filming detergent such as APF Orange Clean. Avoid abrasive cleaners that may dull the surface. Floors may be mopped or scrubbed with a floor machine with a soft brush. Fantastic or 409 may be used if required and mild solvents such as paint thinner may be used for spot cleaning. Floors with a polyurethane finish are not normally waxed, however, waxing is permissible if desired. Periodic reglazing with polyurethane will completely renew the surface. This should be done in strict accordance with the manufacturer's written instructions.

Epoxy or Polyurethane Finishes - Cleaning should be accomplished using a non-filming detergent such as APF Orange Clean. Avoid abrasive cleaners that may dull the surface. Floors may be mopped or scrubbed with a floor machine with a soft brush. Exterior floors may be washed with 2000-2500 psi pressure washer. Pressure washing with hot water is not recommended. Fantastic or 409 may be used if required and mild solvents such as paint thinner may be used for spot cleaning. Periodic recoating will completely renew the surface. This should be done in strict accordance with the manufacturer's written instructions.