



MATERIAL SAFETY DATA SHEET

APF Acryseal VOC

SECTION I

Product Identification and General Information

Product Name: APF Acryseal VOC
Product Class: Clear Acrylic Lacquer
HMIS Codes: H F R P
2 3 1 G

Date Prepared: 11/10/2009
24 Hour Emergency
Assistance: 1-800-562-4921

SECTION II

Hazardous Ingredients

| <u>Hazardous Ingredients</u> | <u>CAS#</u> | <u>OSHA PEL</u> | <u>ACGIH TLV</u> |
|--------------------------------|-------------|-----------------|------------------|
| Acetone | 67-64-1 | 1000 ppm | 1000 ppm |
| P-Chlorobenzotrifluoride | 98-56-6 | N/E | N/E |
| Aromatic Petroleum Distillates | 6472-95-6 | N/E | N/E |

SECTION III

Physical Data

Boiling Point: N/A
Vapor Pressure: 88mm Hg
Vapor Density: Greater than air
Specific Gravity: 0.91
Percent Volatiles: 75%

Solubility in Water: Soluble
Evaporation Rate: 8 (N-butyl Acetate)
Appearance: Clear liquid
Odor: Solvent odor

SECTION IV

Fire and Explosion Hazard Data

Flash Point: Greater than 20° F (TCC)
Flammable Limits:
LEL: 2.6%
UEL: 12.8%
Extinguishing media: Dry chemical, carbon dioxide, foam.
Hazardous Combustion Products: None known.
Special Fire Fighting Procedures: Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear. Use water spray to cool containers exposed to fire.
Fire and Explosion Hazards: Vapors can travel to a source of ignition and flash back.

SECTION V

Reactivity Data

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: None known

