

## SAFETY DATA SHEET

FP325BWH00

Page 1 of 7

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

#### MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING  
4565 W WATKINS ST.  
PHOENIX, AZ 85043 .

TRADE NAME: POLYURETHANE 325 PART B  
COLOR: WHITE AND TINTS  
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### GLOBALLY HARMONIZED SYSTEM (GHS)

##### CLASSIFICATION:

SKIN CORROSION: CATEGORY 1

EYE DAMAGE: CATEGORY 1

SKIN SENSITIZATION: CATEGORY 1

CARCINOGENICITY: CATEGORY 2

ACUTE TOXICITY, ORAL: CATEGORY 4

ACUTE TOXICITY, DERMAL: CATEGORY 4

AQUATIC TOXICITY: CATEGORY 3

#### GHS LABEL ELEMENTS

##### HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

#### HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H351: SUSPECTED OF CAUSING CANCER

H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

#### PRECAUTIONARY STATEMENTS:

##### PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE

P273: AVOID RELEASE TO ENVIRONMENT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

## SAFETY DATA SHEET

FP325BWH00

Page 2 of 7

### SECTION 2: HAZARDS IDENTIFICATION CON'T.

**RESPONSE**

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.  
 P303+P361+353: **IF ON SKIN (OR HAIR):** REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER  
 P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.  
 P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING  
 P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING  
 P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION  
 P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE  
 P391: COLLECT SPILLAGE

**STORAGE**

P405: STORE LOCKED UP

**DISPOSAL**

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

**EMERGENCY OVERVIEW:** CAUTION!  
 RISK OF SERIOUS DAMAGE TO EYES  
 HARMFUL IN CONTACT WITH SKIN  
 HARMFUL IF SWALLOWED  
 CORROSIVE  
 COMPONENTS OF THE PRODUCT MAY EFFECT THE NERVOUS SYSTEM  
 SEVERE EYE IRRITANT  
 SEVERE SKIN IRRITANT  
 MAY CAUSE SENSITIZATION BY SKIN CONTACT

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	40-70	054914-37-3
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	30-60	088917-22-0
MODIFIED CARBONATE BIS-OXAZOLIDINE	1-5	045899-78-1
TITANIUM DIOXIDE	0-20	013463-67-7
IRON (III) OXIDE	0-10	001309-37-1
CARBON BLACK	0-10	001333-86-4

### SECTION 4: FIRST AID MEASURES

**GENERAL:** REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

**EYES:** FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

**SKIN:** REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

**INHALATION:** MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

**INGESTION:** GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

## SAFETY DATA SHEET

FP325BWH00

Page 3 of 7

### SECTION 5: FIRE FIGHTING MEASURES

**FLASH POINT:** 85°C (185°F) – PMCC

**OSHA CLASS:** IIIB

**CONDITIONS OF FLAMMABILITY:** NA

**AUTO IGNITION TEMP.:** NA

**FLAMMABLE LIMITS:** LEL: NE UEL: NE

**SENSITIVITY TO IMPACT:** NONE

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, NH<sub>3</sub>, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

**SENSITIVITY TO STATIC DISCHARGE:** NONE

**EXTINGUISHING MEDIA:** IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

**SPECIAL FIRE FIGHTING PROCEDURES:** NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

### SECTION 7: HANDLING AND STORAGE

**HANDLING:** AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

**STORAGE:** KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

### SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
136210-32-7	NE	NE	NE	NE	
088917-22-0	NE	NE	NE	NE	
045899-78-1	NE	NE	NE	NE	
013463-67-7	10mg/m <sup>3</sup>	ND	10mg/m <sup>3</sup>	ND	(SEE NOTE 1)
001309-37-1	5mg/m <sup>3</sup>	ND	5mg/m <sup>3</sup>	ND	(SEE NOTE 1)
001333-86-4	3.5mg/m <sup>3</sup>	ND	3.5mg/m <sup>3</sup>	ND	(SEE NOTE 1)

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
 NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**ENGINEERING CONTROLS:** NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

## SAFETY DATA SHEET

FP325BWH00

Page 4 of 7

### SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION CON'T.

**RESPIRATORY PROTECTION:** NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

**PROTECTIVE GLOVES:** NITRILE RUBBER

**EYE PROTECTION:** SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** 302°C (572°F)

**VAPOR PRESSURE:** ND

**VAPOR DENSITY:** ND  
(AIR = 1)

**SOLUBILITY IN WATER:** <1%

**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND

**APPEARANCE AND ODOR:** PIGMENTED LIQUID. AMMONIACAL ODOR.

**% VOLATILES BY VOLUME:** 31%

**SPECIFIC GRAVITY:** 1.6-1.75

**MELTING POINT:** 0°C (32°F)

**EVAPORATION RATE:** ND  
(BUTYL ACETATE = 1)

**pH:** NE (ALKALINE)

**ODOR THRESHOLD:** ND

**% SOLIDS BY WEIGHT:** 82%

### SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** AVOID ELEVATED TEMPERATURES

**INCOMPATIBILITY (MATERIAL TO AVOID):** OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** NONE KNOWN

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR

### SECTION 11: TOXICOLOGICAL INFORMATION

**LIKELY ROUTES OF EPOSURE:** EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

**EYES:**

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

**SKIN CONTACT:**

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

**SKIN ABSORPTION:**

ACUTE – ND

CHRONIC – ND

**SAFETY DATA SHEET**

**SECTION 11: TOXICOLOGICAL INFORMATION CON'T.**

**INHALATION:**

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.  
 CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

**INGESTION:**

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT  
 CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

**ACUTE TOXICITY:** NO DATA ON THE PRODUCT ITSELF

**ACUTE ORAL TOXICITY- COMPONENTS**

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LD50: 4150 mg/kg	SPECIES: RAT
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	LD50: >5000 mg/kg	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	LD50: >2000 mg/kg	SPECIES: RAT

**ACUTE DERMAL TOXICITY- COMPONENTS**

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LD50: >5000 mg/kg	SPECIES: RAT
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	LD50: >2000 mg/kg	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	LD50: >2000 mg/kg	SPECIES: RAT

**ACUTE INHALATION TOXICITY- COMPONENTS**

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LC50 (4HR): > 4.178mg/l	SPECIES: RAT
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	LC50/(4HR): 5.7 mg/l	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	ND	

OECD TEST GUIDELINE 403

**SKIN CORROSION/IRRITATION**

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

**SERIOUS EYE DAMAGE/EYE IRRITATION**

SEVERE EYE IRRITATION

**SENSITIZATION**

FOR SKIN SENSITIZATION:

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

FOR RESPIRATORY SENSITIZATION:

NOT CLASSIFIED BUT POSSIBLE DUE TO SKIN SENSITIZATION EFFECT

**SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)**

ND

**SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)**

ND

**CARCINOGENIC DATA: NTP:** NONE

**OSHA:** NONE

**IARC:** YES 2B

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

**SECTION 12: ECOLOGICAL INFORMATION**

**TOXICITY**

**AQUATIC TOXICITY:** NO DATA ON THE PRODUCT ITSELF

**SAFETY DATA SHEET**

**SECTION 12: ECOLOGICAL INFORMATION CONT.**

**ACUTE TOXICITY TO FISH- COMPONENTS**

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LC50 (96 HRS): >100 mg/l	SPECIES: ZEBRAFISH
DPM ACETATE	LC50 (96 HRS): 151 mg/l	SPECIES: FATHEAD MINNOW
MODIFIED CARBONATE BIS-OXAZOLIDINE	LC50 (96 HRS): 9.22 mg/l	SPECIES: FATHEAD MINNOW

**ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS**

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	EC50 (72 HRS): 22.2 mg/l	SPECIES: DAPHNIA MAGNA
DPM ACETATE	EC50 (48 HRS): 2701 mg/l	SPECIES: DAPHNIA MAGNA
MODIFIED CARBONATE BIS-OXAZOLIDINE	EC50 (48 HRS): 6.14 mg/l	SPECIES: DAPHNIA MAGNA

**ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS**

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	EC50 (72 HRS): 73.6 mg/l	SPECIES: FRESH WATER ALGAE
DPM ACETATE	EC50 (72 HRS): >1000 mg/l	SPECIES: GREEN ALGAE
MODIFIED CARBONATE BIS-OXAZOLIDINE	ND	

**TOXICITY TO BACTERIA: COMPONENTS: ND**

**CHRONIC AQUATIC TOXICITY**

**CHRONIC TOXICITY TO AQUATIC INVERTEBRATES**

LONG LASTING ADVERSE EFFECTS TO AQUATIC ORGANISMS

**PERSISTANCE AND DEGRADABILITY**

**BIODEGRADABILITY:** BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

**BIODEGRADATION:** 13%

**EXPOSURE TIME:** 28 DAYS

**METHOD:** OECD TEST GUIDELINE 301B OR EQUIVALENT

**BIOACCUMULATIVE POTENTIAL**

**BIOACCUMULATION:** ND

**PARTITION COEFFICIENT: N-OCTANOL/WATER (LOG P<sub>ow</sub>):** ND

**MOBILITY IN SOIL: ND**

**PARTITION COEFFICIENT (K<sub>oc</sub>):** ND

**SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHODS:** INCINERATION IS PREFERRED. THIS PRODUCT SHOULD NOT BE ALLOWED TO ENTER DRAINS, WATER COURSES OR THE SOIL. PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

**SECTION 14: TRANSPORT INFORMATION**

**DOT PROPER SHIPPING NAME:**

AMINES, LIQUID, CORROSIVE, (BLOCKED DIAMINE,)

**HAZARD CLASS:** 8

**UN NUMBER:** UN 2735

**PACKING GROUP:** III

**IMO SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (BLOCKED DIAMINE), 8, PG III

**ICAO/IATA SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (BLOCKED DIAMINE), 8, PG III

**PASSENGER AIR MAX QUANTITY:** 5L

**PASSENGER PACKING INSTRUCTION:** 852

**CARGO AIR- MAX QUANTITY:** 60L

**CARGO AIR INSTRUCTION NUMBER:** 856

