

SAFETY DATA SHEET

FP325BCL00

Page 1 of 7

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING
4565 W WATKINS ST.
PHOENIX, AZ 85043 .

TRADE NAME: POLYURETHANE 325 PART B
COLOR: CLEAR
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION:

SKIN CORROSION: CATEGORY 1

EYE DAMAGE: CATEGORY 1

SKIN SENSITIZATION: CATEGORY 1

CARCINOGENICITY: CATEGORY 2

ACUTE TOXICITY, ORAL: CATEGORY 4

ACUTE TOXICITY, DERMAL: CATEGORY 4

AQUATIC TOXICITY: CATEGORY 3

GHS LABEL ELEMENTS

HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H351: SUSPECTED OF CAUSING CANCER

H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

PRECAUTIONARY STATEMENTS:

PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE

P273: AVOID RELEASE TO ENVIRONMENT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

SAFETY DATA SHEET

FP325BCL00

Page 2 of 7

SECTION 2: HAZARDS IDENTIFICATION CON'T.

RESPONSE

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.
 P303+P361+353: **IF ON SKIN (OR HAIR):** REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER
 P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.
 P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING
 P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING
 P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION
 P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE
 P391: COLLECT SPILLAGE

STORAGE

P405: STORE LOCKED UP

DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

EMERGENCY OVERVIEW: CAUTION!
 RISK OF SERIOUS DAMAGE TO EYES
 HARMFUL IN CONTACT WITH SKIN
 HARMFUL IF SWALLOWED
 CORROSIVE
 COMPONENTS OF THE PRODUCT MAY EFFECT THE NERVOUS SYSTEM
 SEVERE EYE IRRITANT
 SEVERE SKIN IRRITANT
 MAY CAUSE SENSITIZATION BY SKIN CONTACT

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS
--

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	40-70	054914-37-3
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	30-60	088917-22-0
MODIFIED CARBONATE BIS-OXAZOLIDINE	1-5	045899-78-1
TITANIUM DIOXIDE	0-20	013463-67-7
IRON (III) OXIDE	0-10	001309-37-1
CARBON BLACK	0-10	001333-86-4

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

SAFETY DATA SHEET

FP325BCL00

Page 3 of 7

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 85°C (185°F) – PMCC

OSHA CLASS: IIIB

CONDITIONS OF FLAMMABILITY: NA

AUTO IGNITION TEMP.: NA

FLAMMABLE LIMITS: LEL: NE UEL: NE

SENSITIVITY TO IMPACT: NONE

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂, NH₃, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHING MEDIA: IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

HANDLING: AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

STORAGE: KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
136210-32-7	NE	NE	NE	NE	
088917-22-0	NE	NE	NE	NE	
045899-78-1	NE	NE	NE	NE	
013463-67-7	10mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)
001309-37-1	5mg/m ³	ND	5mg/m ³	ND	(SEE NOTE 1)
001333-86-4	3.5mg/m ³	ND	3.5mg/m ³	ND	(SEE NOTE 1)

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
 NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

SAFETY DATA SHEET

FP325BCL00

Page 4 of 7

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION CON'T.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 302°C (572°F)

SPECIFIC GRAVITY: 1.6-1.75

VAPOR PRESSURE: ND

MELTING POINT: 0°C (32°F)

VAPOR DENSITY: ND
(AIR = 1)

EVAPORATION RATE: ND
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: <1%

pH: NE (ALKALINE)

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

ODOR THRESHOLD: ND

APPEARANCE AND ODOR: PIGMENTED LIQUID. AMMONIACAL ODOR.

% VOLATILES BY VOLUME: 31%

% SOLIDS BY WEIGHT: 82%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

SKIN CONTACT:

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

SAFETY DATA SHEET

SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

INHALATION:

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.
 CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

INGESTION:

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT
 CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

ACUTE TOXICITY: NO DATA ON THE PRODUCT ITSELF

ACUTE ORAL TOXICITY- COMPONENTS

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LD50: 4150 mg/kg	SPECIES: RAT
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	LD50: >5000 mg/kg	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	LD50: >2000 mg/kg	SPECIES: RAT

ACUTE DERMAL TOXICITY- COMPONENTS

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LD50: >5000 mg/kg	SPECIES: RAT
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	LD50: >2000 mg/kg	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	LD50: >2000 mg/kg	SPECIES: RAT

ACUTE INHALATION TOXICITY- COMPONENTS

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LC50 (4HR): > 4.178mg/l	SPECIES: RAT
DIPROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	LC50/(4HR): 5.7 mg/l	SPECIES: RAT
MODIFIED CARBONATE BIS-OXAZOLIDINE	ND	

OECD TEST GUIDELINE 403

SKIN CORROSION/IRRITATION

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

SERIOUS EYE DAMAGE/EYE IRRITATION

SEVERE EYE IRRITATION

SENSITIZATION

FOR SKIN SENSITIZATION:

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

FOR RESPIRATORY SENSITIZATION:

NOT CLASSIFIED BUT POSSIBLE DUE TO SKIN SENSITIZATION EFFECT

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

ND

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

ND

CARCINOGENIC DATA: NTP: NONE

OSHA: NONE

IARC: YES 2B

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

AQUATIC TOXICITY: NO DATA ON THE PRODUCT ITSELF

SAFETY DATA SHEET

SECTION 12: ECOLOGICAL INFORMATION CONT.

ACUTE TOXICITY TO FISH- COMPONENTS

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	LC50 (96 HRS): >100 mg/l	SPECIES: ZEBRAFISH
DPM ACETATE	LC50 (96 HRS): 151 mg/l	SPECIES: FATHEAD MINNOW
MODIFIED CARBONATE BIS-OXAZOLIDINE	LC50 (96 HRS): 9.22 mg/l	SPECIES: FATHEAD MINNOW

ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	EC50 (72 HRS): 22.2 mg/l	SPECIES: DAPHNIA MAGNA
DPM ACETATE	EC50 (48 HRS): 2701 mg/l	SPECIES: DAPHNIA MAGNA
MODIFIED CARBONATE BIS-OXAZOLIDINE	EC50 (48 HRS): 6.14 mg/l	SPECIES: DAPHNIA MAGNA

ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS

ISOPHORONEDIAMINE-ISOBUTYRALDIMINE	EC50 (72 HRS): 73.6 mg/l	SPECIES: FRESH WATER ALGAE
DPM ACETATE	EC50 (72 HRS): >1000 mg/l	SPECIES: GREEN ALGAE
MODIFIED CARBONATE BIS-OXAZOLIDINE	ND	

TOXICITY TO BACTERIA: COMPONENTS: ND

CHRONIC AQUATIC TOXICITY

CHRONIC TOXICITY TO AQUATIC INVERTEBRATES

LONG LASTING ADVERSE EFFECTS TO AQUATIC ORGANISMS

PERSISTANCE AND DEGRADABILITY

BIODEGRADABILITY: BASED ON STRINGENT OECD TEST GUIDELINES, THIS MATERIAL CANNOT BE CONSIDERED READILY BIODEGRADABLE; HOWEVER, THESE RESULTS DO NOT NECESSARILY MEAN THAT THE MATERIAL IS NOT BIODEGRADABLE UNDER ENVIRONMENTAL CONDITIONS.

BIODEGRADATION: 13%

EXPOSURE TIME: 28 DAYS

METHOD: OECD TEST GUIDELINE 301B OR EQUIVALENT

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: ND

PARTITION COEFFICIENT: N-OCTANOL/WATER (LOG P_{ow}): ND

MOBILITY IN SOIL: ND

PARTITION COEFFICIENT (K_{oc}): ND

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: INCINERATION IS PREFERRED. THIS PRODUCT SHOULD NOT BE ALLOWED TO ENTER DRAINS, WATER COURSES OR THE SOIL. PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME:

AMINES, LIQUID, CORROSIVE, (BLOCKED DIAMINE,)

HAZARD CLASS: 8

UN NUMBER: UN 2735

PACKING GROUP: III

IMO SHIPPING DATA:

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (BLOCKED DIAMINE), 8, PG III

ICAO/IATA SHIPPING DATA:

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (BLOCKED DIAMINE), 8, PG III

PASSENGER AIR MAX QUANTITY: 5L

PASSENGER PACKING INSTRUCTION: 852

CARGO AIR- MAX QUANTITY: 60L

CARGO AIR INSTRUCTION NUMBER: 856

