

## SAFETY DATA SHEET

FE4BTT00

Page 1 of 7

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

#### MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING  
4565 W WATKINS ST.  
PHOENIX, AZ 85043 .

TRADE NAME: EPOXY 400 PART B THIXOTROPIC  
COLOR: CLEAR  
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

### SECTION 2: HAZARDS IDENTIFICATION

#### GLOBALLY HARMONIZED SYSTEM (GHS)

##### CLASSIFICATION:

SKIN CORROSION: CATEGORY 1C

EYE DAMAGE: CATEGORY 1

#### GHS LABEL ELEMENTS

##### HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

#### HAZARD STATEMENTS

H302+H312: HARMFUL IN CONTACT WITH SKIN OR IF SWALLOWED

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H411: TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS

#### PRECAUTIONARY STATEMENTS:

##### PREVENTION

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

##### RESPONSE

P303+P352: **IF ON SKIN:** WASH WITH PLENTY OF SOAP AND WATER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING

P301+P331: **IF SWALLOWED:** RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: **IF EYE IRRITATION PERSISTS:** GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

## SAFETY DATA SHEET

FE4BTT00

Page 2 of 7

### SECTION 2: HAZARDS IDENTIFICATION CON'T.

**DISPOSAL**

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

**OTHER HAZARDS**

NO DATA AVAILABLE

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	Wt. %	CAS Number
POLYOXYPROPYLENEDIAMINE	40-70	009046-10-0
NONYLPHENOL	30-60	025154-52-3
1,3-CYCLOHEXANEDIMETHANAMINE	10-30	002579-20-6
BENZYL ALCOHOL	1-5	000100-51-6
SILICON DIOXIDE (AMORPHOUS)	1-5	112945-52-5

### SECTION 4: FIRST AID MEASURES

**GENERAL:** REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

**EYES:** FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

**SKIN:** REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

**INHALATION:** MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

**INGESTION:** GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

### SECTION 5: FIRE FIGHTING MEASURES

**FLASH POINT:** 121°C (250°F) – PMCC

**OSHA CLASS:** IIIB

**CONDITIONS OF FLAMMABILITY:** NA

**AUTO IGNITION TEMP.:** NA

**FLAMMABLE LIMITS:** **LEL:** NE **UEL:** NE

**SENSITIVITY TO IMPACT:** NONE

**HAZARDOUS COMBUSTION PRODUCTS:** CO, CO<sub>2</sub>, NH<sub>3</sub>, NITROGEN OXIDES CAN BE PRODUCED IF HEATED, BURNED OR REACTED WITH INCOMPATIBLE MATERIALS. NITROGEN OXIDES CAN REACT WITH WATER VAPORS TO FORM CORROSIVE NITRIC ACID.

**SENSITIVITY TO STATIC DISCHARGE:** NONE

**EXTINGUISHING MEDIA:** IGNITION MAY GIVE RISE TO A CLASS B FIRE. IN CASE OF FIRE USE: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.

**SPECIAL FIRE FIGHTING PROCEDURES:** NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

## SAFETY DATA SHEET

FE4BTT00

Page 3 of 7

### SECTION 5: FIRE FIGHTING MEASURES

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS:** MAY GENERATE TOXIC OR IRRITATING COMBUSTION PRODUCTS. SUDDEN REACTION AND FIRE MAY RESULT IF PRODUCT IS MIXED WITH AN OXIDIZING AGENT.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** SHUT OFF SOURCES OF IGNITION. COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

### SECTION 7: HANDLING AND STORAGE

**HANDLING:** AVOID CONTACT WITH SKIN AND EYES. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE. ADHERE TO WORK PRACTICE RULES ESTABLISHED BY GOVERNMENT REGULATIONS. USE PERSONAL PROTECTIVE EQUIPMENT. WHEN USING DO NOT EAT, DRINK OR SMOKE.

**STORAGE:** KEEP AWAY FROM OXIDIZERS, HEAT OR FLAME. STORE IN STEEL CONTAINERS. DO NOT STORE NEAR ACIDS. KEEP CONTAINERS TIGHTLY CLOSED IN A DRY, COOL AND WELL-VENTILATED PLACE.

### SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
009046-10-0	NE	NE	NE	NE	
025154-52-3	NE	NE	NE	NE	
002579-20-6	NE	NE	NE	NE	
000100-51-6	NE	NE	NE	NE	
112945-52-5	NE	NE	NE	NE	

**LEGEND:** (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK  
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**ENGINEERING CONTROLS:** NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

**RESPIRATORY PROTECTION:** NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

**PROTECTIVE GLOVES:** NITRILE RUBBER

**EYE PROTECTION:** SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

**OTHER PROTECTIVE EQUIPMENT:** LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**BOILING POINT:** 260°C (500°F)

**SPECIFIC GRAVITY:** 0.96

**VAPOR PRESSURE:** ND

**MELTING POINT:** 0°C (32°F)

**VAPOR DENSITY:** ND  
(AIR = 1)

**EVAPORATION RATE:** ND  
(BUTYL ACETATE = 1)

**SOLUBILITY IN WATER:** <1%

**pH:** NE (ALKALINE)

## SAFETY DATA SHEET

FE4BTT00

Page 4 of 7

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES CONT.

**COEFFICIENT of WATER/OIL DISTRIBUTION:** ND

**ODOR THRESHOLD:** ND

**APPEARANCE AND ODOR:** CLOUDY CLEAR TO AMBER LIQUID, AMMONIACAL ODOR

**% VOLATILES BY VOLUME:** 0%

**% SOLIDS BY WEIGHT:** 100%

### SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** STABLE

**CONDITIONS TO AVOID:** AVOID ELEVATED TEMPERATURES

**INCOMPATIBILITY (MATERIAL TO AVOID):** OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

**HAZARDOUS DECOMPOSITION PRODUCTS:** NONE KNOWN

**HAZARDOUS POLYMERIZATION (REACTIVITY):** WILL NOT OCCUR

### SECTION 11: TOXICOLOGICAL INFORMATION

**LIKELY ROUTES OF EPOSURE:** EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

**EYES:**

ACUTE – SEVERE IRRITANT. MAY CAUSE BURNS. VAPOR MAY CAUSE LACRIMATION AND REVERSIBLE CORNEAL EDEMA.

CHRONIC– CONJUNCTIVITIS OR CORNEAL DAMAGE.

**SKIN CONTACT:**

ACUTE – UNDILUTED PRODUCT QUICKLY CAUSES IRRITATION. MAY CAUSE CHEMICAL BURNS.

CHRONIC – MAY CAUSE ALLERGIC REACTION/SENSITIZATION, DEFATTING OF SKIN, RASH AND IRRITATION.

**SKIN ABSORPTION:**

ACUTE – ND

CHRONIC – ND

**INHALATION:**

ACUTE – VAPORS MAY CAUSE DAMAGE TO CONTACTED TISSUE AND PRODUCE SCARRING.

CHRONIC- REPEATED AND/OR PROLONGED EXPOSURES CAN CAUSE TIGHTNESS OF CHEST, SHORTNESS OF BREATH AND COUGH.

**INGESTION:**

ACUTE – MAY CAUSE IRRITATION AND BLEEDING OF THE GASTROINTESTINAL TRACT

CHRONIC – SCARRING OF THE AFFECTED TISSUES MAY OCCUR.

**ACUTE TOXICITY**

**ACUTE TOXICITY:** NO DATA ON THE PRODUCT ITSELF

**ACUTE ORAL TOXICITY- COMPONENTS**

POLYOXYPROPYLENEDIAMINE	LD50: 2885 mg/kg	SPECIES: RAT
1,3 CYCLOHEXANAMINE	LD50: 700 mg/kg	SPECIES: RAT
BENZYL ALCOHOL	LD50: 1230 mg/kg	SPECIES: RAT
NONYLPHENOL	LD50: 1604 mg/kg	SPECIES: RAT

**SAFETY DATA SHEET**

**SECTION 11: TOXICOLOGICAL INFORMATION CON'T.**

**ACUTE DERMAL TOXICITY- COMPONENTS**

POLYOXYPROPYLENEDIAMINE	LD50: 2980 mg/kg	SPECIES: RABBIT
1,3 CYCLOHEXANAMINE	LD50: 1700 mg/kg	SPECIES: RABBIT
BENZYL ALCOHOL	LD50: 2000 mg/kg	SPECIES: RABBIT
NONYLPHENOL	LD50: 2031 mg/kg	SPECIES:

**ACUTE INHALATION TOXICITY- COMPONENTS**

POLYOXYPROPYLENEDIAMINE	LC50 (4 HR):> 0.74mg/l	SPECIES:RAT
BENZYL ALCOHOL	LC50 (4 HR): > 4.178mg/l	SPECIES: RAT
	OECD TEST GUIDLINE 403	

**SKIN CORROSION/IRRITATION**

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

**SERIOUS EYE DAMAGE/EYE IRRITATION**

SEVERE EYE IRRITATION

**SENSITIZATION**

BUEHLER SKIN SENSITIZATION (GUINEA PIGS): NO EVIDENCE OF SENSITIZATION AT 5%

FOR RESPIRATORY SENSITIZATION:

ND

**SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)**

ND

**SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)**

ND

**CARCINOGENIC DATA: NTP: NONE**

**OSHA: NONE**

**IARC: NONE**

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

**SECTION 12: ECOLOGICAL INFORMATION**

**TOXICITY**

**AQUATIC TOXICITY:** NO DATA ON THE PRODUCT ITSELF

**ACUTE TOXICITY TO FISH- COMPONENTS**

POLYOXYPROPYLENEDIAMINE	LC50 (96 HRS): 772 mg/l	SPECIES: FISH
1,3 CYCLOHEXANAMINE	LC50 (96 HRS): 130 mg/l	SPECIES: GOLDEN ORFE
BENZYL ALCOHOL	LC50 (96 HRS): 460 mg/l	SPECIES: FATHEAD MINNOW
NONYLPHENOL	LC50 (96HRS): 0.14 mg/l	SPECIES: PIMEPHALES PROMELAS

**ACUTE TOXICITY TO AQUATIC INVERTEBRATES: COMPONENTS**

POLYOXYPROPYLENEDIAMINE	EC50 (48 HRS): 80 mg/l	SPECIES: DAPHNIA MAGNA
1,3 CYCLOHEXANAMINE	EC50 (72 HRS): 33.1 mg/l	SPECIES: DAPHNIA MAGNA
BENZYL ALCOHOL	EC50 (72 HRS): 12 mg/l	SPECIES: DAPHNIA MAGNA
NONYLPHENOL	EC50 (48 HRS): 0.035 mg/l	SPECIES: DAPHNIA MAGNA

**ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: COMPONENTS**

POLYOXYPROPYLENEDIAMINE	EC50 (72 HRS): 15 mg/l	SPECIES: FRESH WATER ALGAE
1,3 CYCLOHEXANAMINE	EC50 (72 HRS): 56.7 mg/l	SPECIES: FRESH WATER ALGAE
BENZYL ALCOHOL	EC50 (72 HRS): 700 mg/l	SPECIES: FRESH WATER ALGAE
NONYLPHENOL	LC50 (72 HRS): 0.056 mg/l	SPECIES: FRESH WATER ALGAE

**SAFETY DATA SHEET**

**SECTION 12: ECOLOGICAL INFORMATION CON'T.**

**TOXICITY TO BACTERIA: COMPONENTS**

POLYOXYPROPYLENEDIAMINE	EC50: 310mg/l	ACTIVATED SLUDGE
1,3 CYCLOHEXANAMINE	EC50: > 1000mg/l	ACTIVATED SLUDGE
NONYLPHENOL	EC50: 950 mg/l	ACTIVATED SLUDGE

**CHRONIC AQUATIC TOXICITY**

**CHRONIC TOXICITY TO AQUATIC INVERTEBRATES**

LONG LASTING ADVERSE EFFECTS TO AQUATIC ORGANISMS

**PERSISTANCE AND DEGRADABILITY**

**BIODEGRADABILITY:** NOT BIODEGRADABLE.

**BIODEGRADATION:** 0%

**EXPOSURE TIME:** 28 DAYS

**METHOD:** OECD TEST GUIDLINE 301B OR EQUIVALENT

**BIOACCUMULATIVE POTENTIAL**

**BIOACCUMULATION:**

**PARTITION COEFFECIENT:** N-OCTANOL/WATER(LOG P<sub>ow</sub>): 1.34

**MOBILITY IN SOIL**

ND

**SECTION 13: DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHODS:** INCINERATION IS PREFERRED. COMPLY WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. CHEMICAL AND/OR BIOLOGICAL DEGRADATION IS FEASIBLE.

**SECTION 14: TRANSPORT INFORMATION**

**DOT PROPER SHIPPING NAME:**

AMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE)

**HAZARD CLASS:** 8

**UN NUMBER:** UN 2735

**PACKING GROUP:** III

**IMO SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE), 8, PG III

**ICAO/IATA SHIPPING DATA:**

UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (POLYOXYPROPYLENEDIAMINE), 8, PG III

**ADDITIONAL INFORMATION:** NONE

**SECTION 15: REGULATORY INFORMATION**

**VOC: COMPONENT:** 0 grams/Liter      **AS APPLIED:** 0 grams/Liter (PART OF MULTI-COMPONENT SYSTEM)

**TSCA (TOXIC SUBSTANCE CONTROL ACT):** ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT):** ND

**SARA TITLE III**

**SECTION 312 HAZARD CLASS:** IMMEDIATE (ACUTE) HEALTH HAZARD, DELAYED (CHRONIC) HEALTH HAZARD

**SECTION 313 LISTED INGREDIENTS:** PHENOL

**CALIFORNIA PROPOSITION 65:** THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE.



**SAFETY DATA SHEET**

FE4BTT00

Page 7 of 7

**SECTION 16: OTHER INFORMATION**

**INITIAL ISSUE DATE:** MAY 11, 2015

**REVISION DATE:**

**PREPARED BY:** J.W. ESSIG

**HAZARD RATING**

**HMIS:**                                      **HEALTH**    **2**                      **FLAMMABILITY**    **1**                      **REACTIVITY**    **1**

**LEGEND**

- ACGIH:            AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
- OSHA:            OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
- STEL:            SHORT TERM EXPOSURE LIMIT
- TWA:            TIME WEIGHTED AVERAGE
- PEL:            PERMISSIBLE EXPOSURE LIMIT
- TLV:            THRESHOLD LIMIT VALUE
- NA:            NOT APPLICABLE
- NE:            NOT ESTABLISHED
- ND:            NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.